











Circuit Breakers for Equipment

Type	Number of poles	Rated voltage	Current range	Application				Protection				Options				Con-nection		Mounting										
				General purpose	Industrial applications	Power supply	Household and leisure	Thermal	Thermal-Magnetic	Available without protection	Undervoltage protection	Illumination	Different printings	Auxiliary contact	Shunt contact	Remote tripping	Quick connect terminals	Screw terminals	PCB THT	Threaded neck	Snap-in front side	Snap-in rear side	Drop-in type	Flange type				
 T9-611 Reset type, glow-wire version optional	1	240 VAC 48/32 VDC	3-16 A	•	•	•		•							•		•											
 T9-311 / 211 Reset type, glow-wire version optional	1	240 VAC 48/32 VDC	3-16 A	•	•	•		•									•											
 T9-711 Reset type, glow-wire version optional	1	240 VAC 48/32 VDC	3-16 A	•	•	•		•									•											
 T9-818 Reset type, glow-wire version optional	1	240 VAC 48/32 VDC	3-15 A	•	•	•		•										•										
 T9-817 Reset type, glow-wire version optional	1	240 VAC 48/32 VDC	3-12 A	•	•	•		•										•										
 T11 Reset type	1	240 VAC 48 VDC	0.05A-16 A	•	•	•		•							•		•											
 T12 Reset- or switch type	1	240 VAC 28 VDC	0.05-16 A	•	•	•		•							•	•	•	•										•
 T12-MSM Reset- or switch type	1	240 VAC 28 VDC	0.05-16 A	•	•	•		•							•	•	•	•										
 TM12 Reset- or switch type	1	240 VAC 28 VDC	0.05-16 A	•	•	•		•	•						•	•	•	•										•
 TM12-MSM Reset- or switch type	1	240 VAC 28 VDC	0.05-16 A	•	•	•		•	•						•	•	•	•										
 T13 Reset- or switch type	1	250 VAC 28 VDC	0.05-30 A	•	•	•		•									•	•										
 TA35 Switch type	1	240 VAC 32 VDC	0.05-20 A	•	•	•	•	•		•		•	•				•											
 TA35 Switch type	2	240 VAC 60 VDC	0.05-20 A	•	•	•	•	•		•		•	•				•											
 TA35 Switch type	3	240 VAC	0.05-12 A	•	•	•	•	•		•		•	•				•											
 TA45 Switch type	2	240/400 VAC 60 VDC	0.05-20 A	•	•	•	•	•		•	•	•	•	•	•	•	•											•
 TA45 Switch type	3	240/400 VAC 60 VDC	0.05-12 A	•	•	•	•	•		•	•	•	•	•	•	•	•											•

Power Entry Modules with Circuit Breaker

Type	Current range	IEC 60320-1 inlet type	IEC connector type			Circuit breaker				Mounting			Connection	
			Protection class I	Protection class II	V-Lock cord retaining	CBE 1-pole protected	CBE 2-pole protected	Illuminated rocker	Components prewired	Screw-on front	Screw-on rear	Snap-in	Quick connect	Wire leads on request
 DG11 recessed switch, double pole CBE, optional IP67	1-10A IEC 1-15A UL	C14	•	•	•	•	•	•	•	•	•	•	•	•
 DF11 recessed switch, double pole CBE	1-10A IEC 1-15A UL	C14	•	•	•	•	•	•	•	•	•	•	•	•
 6145 double pole CBE	1-10A IEC 1-15A UL	C14/C18	•	•	•	•	•	•	•	•	•	•	•	•
 6135 double pole CBE	1-10A IEC 1-15A UL	C14	•	•	•	•	•	•	•	•	•	•	•	•
 EF11 recessed switch, double pole CBE	12-16A IEC 12-20A UL	C20	•	•	•	•	•	•	•	•	•	•	•	•
 6136 single pole CBE	12-16A IEC 12-20A UL	C20	•	•	•	•	•	•	•	•	•	•	•	•

Power Entry Modules with Circuit Breaker and Filter

Type	Current range	Inlet	IEC connector type			Circuit breaker				Mounting		Connection		Attenuation		Leakage current	
			Protection class I	Protection class II	V-Lock cord retaining	CBE 1-pole protected	CBE 2-pole protected	Illuminated rocker	Components prewired	Screw front	Snap-in	Quick connect	Wire leads on request	Standard 20 - 50 dB	High 40 - 70 dB	Medical <5µA	Medical <80µA
 DG12 IP67 variants pre-wired, double pole CBE	1-10A IEC 1-15A UL/CSA	C14/C18	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 DF12 recessed switch pre-wired, double pole CBE	1-10A IEC 1-15A UL	C14	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 5145 pre-wired, double pole CBE	1-10A IEC 1-15A UL	C14/C18	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 EF12 recessed switch pre-wired, double pole CBE	12-16A IEC 12-20A UL	C20	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Web information

At schurter.com you can enter the component type (e.g. TA35) into the search box and download the data sheets containing all relevant details.

schurter.com/cp schurter.com/connectors schurter.com/emc

Customized solutions

In addition to its broad product range, SCHURTER also offers individual services to fulfill all customer requirements. We will build specific samples and provide you with your customized solution. Please submit your request using the contact form on our website

schurter.com/contact.